




STEEL WORKERS SPECIFICATIONS



CHANNEL SHEAR




I-BEAM SHEAR




SQUARE BAR SHEAR




ROUND BAR SHEAR




NOTCHING




VEE-NOTCHING




PUNCHING




PUNCHING




PUNCHING



ANGLE BENDING



PRESS BRAKE



FLAT-BAR SHEAR

CAPACITIES AND SPECIFICATIONS FOR STEEL WORKER

UNIT : MM

MODEI	GSW -01	GSW -02	GSW -03
TON	55 TON	80 TON	110TON
CHANNEL / I BIM SHEAR	100 x 50	150 x 75	200 x 100
ANGLE SHEAR	100 x 100 x 8	100 x 100 x 12	130 x 130 x 08
ROUND / SQUARE SHEAR	38mm	45mm	60mm
FLAT BAR SHEAR	300 x 12	430 x 15	530 x 18
PUNCHING	Ø 40 x 06	Ø 40 x 08	Ø 50 x 10
NOTCHING	50 x 40 x 05	60 x 40 x 06	80 x 60 x 06
MOTOR H.P.	5/1440	7.5/1440	15/1440

OPTIONAL TOOLING

NOTE :- Based on material strength 45 kg/ mm² tensil. Design and specification subject to change without notice.

OPTIONAL FEATURES

1. Blade for Round Bar, Square Bar Cutting "i" Section Cutting
2. First fill of Hydraulic oil
3. Main Back Gauge

STANDARD ACCESSORIES

1. Blade for Angle Cutting. Channel Cutting, Flat Cutting G Notching
2. Fine stroke Adjustment Road with Limit Switch
3. Manual Job Clamping Device
4. Electric Control Pannel
5. Pair of Foot Switch
6. Main Drive Motor